



PIPE SIZE	CATALOG #	ID INCHES WITH COATING	OD INCHES WITH COATING	WT PER 100 FEET
1/2"	COND50GG	0.632	0.92	86
3/4"	COND75GG	0.836	1.13	111
1"	COND100GG	1.063	1.395	163
1-1/4"	COND125GG	1.394	1.74	215
1-1/2"	COND150GG	1.624	1.98	262
2"	COND200GG	2.083	2.455	354
2-1/2"	COND250GG	2.489	2.955	542
3"	COND300GG	3.09	3.58	705
3-1/2"	COND350GG	3.57	4.08	847
4"	COND400GG	4.05	4.58	999
5"	COND500GG	5.073	5.643	1332
6"	COND600GG	6.093	6.705	1989

Galvanized Rigid Conduit

HOW TO ORDER

All Nipples have the prefix of NPL

1. Add the conduit size needed to the prefix

1/2" → NPL50

2. Enter an "X" to represent "by" for a length

NPL50X

3. Enter the desired nipple length

NPL50X6

4. Determine the proper suffix

- For coated steel nipples use the suffix GG

- For coated aluminum nipples use the suffix ALGG

NPL50X6GG

NPL50X6ALGG

GRC COATED CONDUIT



COATED NIPPLE



SPECIFICATIONS

- 40 mil Polyolefin exterior coating
- 2 mil Thermoset Polymer interior
- Sealing boots for conduit
- No VOCs
- No Halogens

Compliances

- UL Standard 6
- Meets or Exceeds NEMA RN-1
- Rated for Direct Burial & Concrete Encasement

Dimension and Specifications are subject to change without notice