



GRC Coated Couplings




Galvanized Rigid Conduit

SPECIFICATIONS

- 40 mil Polyolefin exterior coating
- Sealing boots for conduit

COMPLIANCES

- UL Standard 6
 - Meets or Exceeds NEMA RN-1
- No VOCs
- No Halogens
- Rated for Direct Burial & Concrete Encasement



PIPE SIZE	CATALOG #	OD. INCHES	a	b	Wt
			Metal Length	Coating Sleeve	
1/2"	CPL50GG	1.244	1.5	0.75	18
3/4"	CPL75GG	1.251	1.532	0.747	30
1"	CPL100GG	1.771	1.906	0.94	38
1-1/4"	CPL125GG	2.146	1.906	1.03	47
1-1/2"	CPL150GG	2.459	1.906	1.03	66
2"	CPL200GG	2.959	1.937	1.157	89
2-1/2"	CPL250GG	3.584	2.878	1.58	118
3"	CPL300GG	4.239	3.031	1.75	211
3-1/2"	CPL350GG	4.865	3.094	1.75	413
4"	CPL400GG	5.239	3.188	1.87	384
5"	CPL500GG	6.069	3.374	1.87	541
6"	CPL600GG	7.269	3.437	2.18	872

Dimension and Specifications are subject to change without notice