



**SPECIFICATIONS**

- Used with locknut to terminate threaded rigid conduit or IMC to enclosure
- 90° C Cu-Al dual rated lay-in lug provided for grounding jumper to neutral bus bar
- Assembled with 150° C rated Nylon insulator to prevent damage to wire insulation during pulling
- Cast of high strength malleable iron and zinc plated
- 20 mil Polyolefin exterior coating

**COATED GROUNDING BUSHINGS WITH LAY-IN LUG**



GROUNDING BUSHINGS					
CATALOG #	TRADE SIZE	SHIPPING QTY	SHIPPING WT./100	MIN WIRE SIZE	MAX WIRE SIZE
GRBUSHING50GG	1/2"	50	8.4	#14	#4
GRBUSHING75GG	3/4"	50	9.9	#14	#4
GRBUSHING100GG	1"	25	13	#14	#4
GRBUSHING125GG	1-1/4"	20	19	#14	#4
GRBUSHING125GG	1-1/4"	20	25.1	#14	#1/0
GRBUSHING150GG	1-1/2"	20	28	#14	#4
GRBUSHING150GG	1-1/2"	20	31.1	#14	#1/0
GRBUSHING200GG	2"	10	38	#14	#4
GRBUSHING200GG	2"	10	44.3	#14	#1/0
GRBUSHING250GG	2-1/2"	5	66.7	#14	#1/0
GRBUSHING250GG	2-1/2"	5	73	#6	#250
GRBUSHING300GG	3"	5	81.7	#14	#1/0
GRBUSHING300GG	3"	5	88	#6	#250
GRBUSHING350GG	3-1/2"	5	90	#14	#1/0
GRBUSHING350GG	3-1/2"	5	96	#6	#250
GRBUSHING400GG	4"	5	113.5	#14	#1/0
GRBUSHING400GG	4"	5	126	#6	#250
GRBUSHING500GG	5"	1	195	#6	#250
GRBUSHING600GG	6"	1	282	#6	#250

\*\*Dimension and Specifications are subject to change without notice\*\*