



SPECIFICATIONS


- 40 mil Polyolefin Exterior Coating
- Sealing boots for conduit
- No VOC's
- No Halogens

COMPLIANCES

- UL Standard 1203
- Class I, Div. 1 & 2, Groups C,D
- Class II, Div. I & 2, Groups E,F,G



COATED CONDUIT UNIONS



UNF

UNY

UNF - FEMALE / FEMALE				
SIZE	CATALOG #	A	B	WT
1/2"	UNF105GG	3.38	1.58	0.4
3/4"	UNF205GG	3.94	1.89	0.7
3/4"-1/2"	UNF215GG	3.69	1.89	0.8
1"	UNF305GG	4.75	1.96	1.3
1-1/4"	UNF405GG	5.69	2.83	2.6
1-1/2"	UNF505GG	6.56	3.14	3.9
2"	UNF605GG	7.75	3.89	4.2
2-1/2"	UNF705GG	8.63	4.39	5.5
3"	UNF805GG	9.01	5.14	7.5
3-1/2"	UNF905GG	9.49	5.77	8.4
4"	UNF1005GG	9.63	6.27	10.5
5"	UNF012GG	9.25	8.27	12
6"	UNF014GG	9.38	9.39	14.9

UNF - MALE / FEMALE				
SIZE	CATALOG #	A	B	WT
1/2"	UNY105GG	3.38	1.58	0.4
3/4"	UNY205GG	3.94	1.89	0.7
3/4"-1/2"	UNY215GG	3.69	1.89	0.8
1"	UNY305GG	4.75	1.96	1.3
1-1/4"	UNY405GG	5.69	2.83	2.6
1-1/2"	UNY505GG	6.56	3.14	3.9
2"	UNY605GG	7.75	3.89	4.2
2-1/2"	UNY705GG	8.63	4.39	5.5
3"	UNY805GG	9.01	5.14	7.5
3-1/2"	UNY905GG	9.49	5.77	8.4
4"	UNY1005GG	9.63	6.27	10.5
5"	UNY012GG	9.25	8.27	12
6"	UNY014GG	9.38	9.39	14.9

Dimension and Specifications are subject to change without notice